







INGUN interchangeable kits for Keysight Inline In-circuit Test Systems

For the **Keysight Inline Incircuit Test Systems Medalist i3070-5i** and **i1000D-SFP** we provide robust interchangeable kits.

Features:

- Bend resistant FR4 probe plate
- ESD-compliant, precision-guided moving plate
- Moving plate, guiding pillars and guiding bushes included
- Coding block for WSO Keysight/i3070-5i included
- Single-sided 1- or 2-stage or double-sided 1-stage contacting

Ordering information and technical information:

	Interchangeable kit for Incircuit test system i3070-5i	Interchangeable kit for Incircuit test system i1000D-SFP
<ul style="list-style-type: none"> - Type: - Description: - Part number: - Outer dimensions (W x D x H): 	Interchangeable kit (WS) complete WS Keysight/i3070-5i 48136-KIT (*) approx. 566 x 403 x 278 mm 	--- --- --- ---
<ul style="list-style-type: none"> - Type: - Description: - Part number: - Outer dimensions (W x D x H): - Thickness of probe plate: 	Interchangeable kit bottom part (WSU) WSU Keysight/i3070-5i 48152 approx. 566 x 403 x 65 mm approx. 14 mm 	Interchangeable kit bottom part (WSU) WSU Keysight/i1000D 53790 approx. 470 x 365 x 125 mm approx. 10 mm 
<ul style="list-style-type: none"> - Type: - Description: - Part number: - Outer dimensions (W x D x H): 	Interchangeable kit top part (WSO) WSO Keysight/i3070-5i 48151 approx. 455 x 341 x 197 mm 	Interchangeable kit top part (WSO) WSO Keysight/i1000D 53910 approx. 459 x 340 x 167 mm 
<ul style="list-style-type: none"> - Max. usable area (W x D): - Pushrod length: - Max. clearance available: <ul style="list-style-type: none"> - Below PCB: - Above PCB: - Installation height GKS bottom: - Installation height GKS top: - Installation height GKS 2-stage bottom: - Test system Interface: 	approx. 405 x 341 mm 20 mm (4 mm countersunk) approx. 2.5 mm approx. 11 mm 16.0 mm 16.0 mm 16.0 21.5 mm not loaded, for max. 3.666 personality pins 	approx. 330 x 290 mm 60 mm approx. 2.5 mm approx. 58 mm 13.0 mm 16.0 mm 13.0 18.3 mm not loaded, for max. 42 VG female sockets 

INGUN interchangeable kits for Keysight Inline In-circuit Test Systems

Recommended accessories for WS Keysight/i3070-5i:

Start-up kit SK-M-20-WS:	Part no.: 50589
Spacer:	Part no.: 48160
Stroke counter WS Keysight/i3070-5i:	Part no.: 48137
ESD-kit (single-stage contacting):	Part no.: 4137

Additionally we offer Keysight-specific accessories for customised assembly, such as:

- Personality pins
- Opens Test Units (TestJets, VTEPs, Polarity Checks)
- Signal-conditioner boards

*: Items with the suffix "-KIT" are not delivered pre-assembled.
This enables easy, immediate customised assembly.

Please contact us for further information.
Prices and delivery time on request.
Technical changes possible without prior notification.

You will find further innovative products on our homepage and in our catalogue. Don't miss our vacuum test fixtures for Keysight Incircuit test systems.

