EXCHANGEABLE KITS


Exchangeable kit **ATS MA09**

Item 45994-KIT





- Quick, tool-free set-up, can be used without readjustment
- Available in standard, ESD, and RF versions, with or without internal interface
- Modularly configurable signal transmission with internal interfaces
- Pressure plate unit and probe plate unit can be screwed together with stacking screws to form a unit with protected probe field
- Robust, durable design
- Can be customised using functional units for individual configurations
- Detailed accompanying documents (e.g., customising guidelines)



General data

Product group: ATS manual test fixture (MA) Subseries: ATS MAXX ATS MA09 Series: Version: Without interface Scope of delivery: Unassembled For tandem fixtures: No Max. interface signals: 0 Interface blocks required: No Max. internal interface blocks: Internal interface: Not available Yes, with compatible additional option Dual-stage contacting: Double-sided contact: Yes, with compatible additional option Weight: 2.25 kg [4.96 lbs] Min. temperature: 10 °C [50 °F] 60 °C [140 °F] Max. temperature: Low voltage: Yes, with suitable additional option RoHS-compliant: Yes

Compatible with

Manual test fixtures (MA): MA x209

Technical data

recrimical data		
Pushrod length:		60 mm [2.36 in]
Test probe installation height,	, top:	16 mm [.629 in]
Test probe installation height,	, bottom:	10.5 mm [.413 in]
Test probe installation height,	, dual-stage, bottom:	16 mm [.629 in]
Free space above PCB:		58 mm [2.28 in]
Useable area (WxD):	150 x 1	70 mm [5.9 x 6.69 in]
Outer dimensionS (WxDxH):	210 x 237 x 197 mm	[8.26 x 9.33 x 7.75 in]


EXCHANGEABLE KITS

Exchangeable kit ATS MA09

Item 45994-KIT







INGUN Prüfmittelbau GmbH Max-Stromeyer-Straße 162 78467, Constance, Germany Phone +49 7531 8105-0 Customer hotline +49 7531 8105-888 Fax +49 7531 8105-65 info@ingun.com









Learn more about MA exchangeable kits

