

Exploded view diagram of the VK VA3070S/i3070 Vacuum Cassette assembly, showing components 1 through 8.

Key components and dimensions:

- Top Plate (1): Dimensions 405,80 x 460,20 mm. Usable area (Nutzfläche) is 315 x 400 mm.
- Moving Plate (2): Dimensions 405,80 x 460,20 mm.
- Vacuum Seal (3): Dimensions 405,80 x 460,20 mm.
- Frame (4): Dimensions 405,80 x 460,20 mm.
- Buttons (5): Dimensions 16,0 x 16,0 mm.
- Guide Pins (6): Dimensions 16,0 x 16,0 mm.
- Guiding Bushes (7): Dimensions 16,0 x 16,0 mm.
- Stroke-limiting Disk (8): Dimensions 16,0 x 16,0 mm.

Assembly instructions:

- For the vacuum seal, a silicone adhesive is recommended, e.g., Elastosil E41 by Wacker.
- Teile sind nicht montiert / Components are not assembled.

Art.-Nr.: Part-no.:	Menge: Amount:	Benennung DE: Description DE:	Benennung EN: Description EN:
114945	1	KTP VA3070S/i3070	KTP VA3070S/i3070 Probe plate
114859	1	ADP VA3070S/i3070	ADP VA3070S/i3070 Moving plate
4911	1	VD-V-2070	VD-V-2070 Vacuum seal
114861	1	Rahmen	Frame
8671	8	Linsenschraube M 3x 5 T10	Button head screw M 3x 5 T10 ISO 7380 - A2
1607	2	Griff Druckplatte	Handle MG-01.089.04
5332	2	Aufkleber "Kein Tragegriff"	Sticker "No carrying handle"
8189	7	Senkschraube M 4x 16 T20	Flat headed screw M 4x 16 T20 ISO 14581 - A2
2229	3	FUS-08-30-ST-M4	FUS-08-30-ST-M4 Guide pin
2196	3	FUB-08-14-35-POM-BL-B	FUB-08-14-35-POM-BL-B Guiding bush
2579	9	HBS-01,0-10,0	HBS-01,0-10,0 Stroke-limiting disk
2676	8	Zyl.-Stift D 4m6x 8	parallel pin D 4m6x 8 ISO 8734 C1 - A2
1571	4	FED-10,0-16,0-97N-09,0	FED-10,0-16,0-97N-09,0 Pressure spring
2924	16	Zyl.-Schraube M 4x 12 T20	Head cap screw M 4x 12 T20 ISO 14579 - A2
22111	1	FB-ALS-VA207x	ESD discharge probe
INFO 4605	1	Label-Typenschild-1010	Label-Typenschild-1010 Label

Maßstab/Scale: 1:5
gespeichert/saved: 01.09.2023 11:36:19
Montageanleitung/instruction sheet

Benennung/Designation:
VK VA3070S/i3070 Vakuumkassette
VK VA3070S/i3070 | Vacuum cassette

Artikel-Nr./PartNo.:
114914

Index: **2**
Blatt/Sheet: 1 von 1
DIN A3