Test Probe

GKS-040 297 040 A 0800

Item GKS-040-0001







- Well-established test probes for contacting PCBs
- For optimal contact to the test points (e.g. pads, vias, and pins), various tip styles with various diameters and finishes are available.
- · Various spring forces available as well as versions with stainless steel springs suitable for high temperatures
- Used for setting the optimum stroke conditions in the test fixture, various installation heights can be achieved by combining test probes and receptacles









General data

RoHS-compliant:

Product group: ICT / FCT (in-circuit test and function test Sub-product group: Standard stroke test probe GKS-040 Series: Grid: 1 mm [39.3 mil]

Contacting from: Yes Magnetic: Plug-in Installation type: Quick-exchange system: Yes Adjustable installation height: No Non-rotating: No Compatible receptacle(s): KS-040 Min. temperature: -40 °C [-40 °F] Max. temperature: 80 °C [176 °F] Tip style data

97 4-edged 90° dagger, self-cleaning Tip style: Tip diameter: 0.4 mm [.015 in] Tip style surface: A gold Tip style material: 2 steel

Electrical data

Current load capacity / rated current: 2 A Typical resistance (Ri): 20 mOhm

Mechanical data


Total length: 35.9 mm [1.41 in] Barrel diameter: 0.61 mm [.024 in] Maximum stroke: 6.35 mm [.25 in] Spring pre-load: 0.15 N [.539 ozf] Collar height: Spring force at working stroke: 0.8 N [2.87 ozf] Recommended working stroke: 4.3 mm [.169 in]

Test Probe GKS-040 297 040 A 0800

Item GKS-040-0001







INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162 78467, Constance, Germany Phone +49 7531 8105-0 Customer hotline +49 7531 8105-888 Fax +49 7531 8105-65 info@ingun.com









Learn more about **ICT/FCT Test probes**

