

High-current test probe

HSS-118 306 180 A 2210

Item HSS-118-0513



GO TO PRODUCT


ingun[®]

Partner for Future Technology

- Trusted, robust high-current probes, optimally sized for current load capacity ratio
- Low-Ohm probe with Ri typical: < 10 mOhm
- For use in function and burn-in tests
- Large selection of tip styles and spring forces for optimum contact with DUT
- Optimum adjustment of the stroke ratios in the test fixture: The test probe collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights



1:1



General data

Product group: Standard HSS (press-in)
 Sub-product group: Standard HSS (press-in)
 Series: HSS-118
 Grid: 2.54 mm [100 mil]
 Contacting from: Post
 Magnetic: Yes
 Installation type: Plug-in
 Quick-exchange system: Yes
 Adjustable installation height: No
 Non-rotating: No
 Compatible receptacle(s): KS-112
 Min. temperature: -100 °C [-148 °F]
 Max. temperature: 200 °C [392 °F]
 RoHS-compliant: Yes

Tip style data

Tip style: 06 serrated
 Tip diameter: 2 mm [0.078 in]
 Tip style surface: A gold
 Tip style material: 3 CuBe

Electrical data

Current load capacity / rated current: 20 A
 Typical resistance (Ri): 10 mOhm

Mechanical data

Total length: 40.3 mm [1.58 in]
 Barrel diameter: 1.66 mm [0.065 in]
 Maximum stroke: 5.3 mm [0.208 in]
 Spring pre-load: 0.61 N [2.19 ozf]
 Collar height: 10
 Spring force at working stroke: 2.25 N [8.09 ozf]
 Recommended working stroke: 4 mm [0.157 in]

HIGH-CURRENT TEST PROBES


High-current test probe HSS-118 306 180 A 2210

Item HSS-118-0513



ingun[®]

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 11/25_GB

Learn more about
High-current test probes



[ingun.com](https://www.ingun.com)

HIGH-CURRENT TEST PROBES