




Verrastprüfung

Zur Überprüfung der korrekten Verrastung des Kontaktterminals im Steckergehäuse



1:1



General data

Screw-in torque max.:
 Product group:
 Sub-product group:
 Series:
 Grid:
 Contacting from:
 Magnetic:
 Installation type:
 Quick-exchange system:
 Adjustable installation height:
 Non-rotating:
 Continuous plunger:
 Screw-in torque:
 Compatible receptacle(s):
 Min. temperature:
 Max. temperature:
 RoHS-compliant:

5 cNm [.442 lbf-in]
 Push-back probes
 Push-back probes
 VF3
 3 mm [118 mil]
 Post
 Yes
 Screw-in
 Yes
 No
 Yes
 $\phi 0.9 \times 0.6 \times 7.0$
 3 – 5 cNm [.265 – .442 lbf-in]
 KS-VF3
 -40 °C [-40 °F]
 80 °C [176 °F]
 Yes

Tip style data

Tip style:
 Tip diameter:
 Tip style surface:
 Tip style material:

06 serrated
 2.7 mm [.106 in]
 A gold
 2 steel

Electrical data

Current load capacity / rated current:
 Typical resistance (Ri):

8 A
 30 mOhm

Mechanical data

Total length:
 Barrel diameter:
 Maximum stroke:
 Spring pre-load:
 Spring force at working stroke:
 Recommended working stroke:

69.7 mm [2.74 in]
 2.19 mm [.086 in]
 5.5 mm [.216 in]
 5.96 N [21.4 ozf]
 15 N [53.9 ozf]
 5 mm [.196 in]

Test Probe


VF3-206 270 A 405 15

Item VF3-0021



ingun[®]

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 12/25_GB

Learn more about
Screw-in test probe



ingun.com

SCREW-IN TEST PROBE