







GO TO PRODUCT

- Robust test probes with continuous plunger for applications with unwanted side and axial forces
- For use in applications with limited space



General data

Product group:	Assorted test probes
Sub-product group:	Short stroke GKS / charge and transfer GKS
Series:	GKS-364
Grid:	6.5 mm [255 mil]
Contacting from:	Post
Magnetic:	Yes
Installation type:	Plug-in
Quick-exchange system:	No
Type of test probe connection:	Plug
Adjustable installation height:	No
Non-rotating:	No
Continuous plunger:	Ø1,3 x 8,0
Compatible connector(s):	SE-503
Compatible receptacle(s):	KS-364
Min. temperature:	-100 °C [-148 °F]
Max. temperature:	200 °C [392 °F]
RoHS-compliant:	Yes

Tip style data

Tip style:	06 serrated
Tip diameter:	4 mm [.157 in]
Tip style surface:	N nickel
Tip style material:	2 steel

Electrical data

Current load capacity / rated current:	8 A
Current rating, connection on plunger:	15 A
Typical resistance (Ri):	30 mOhm
Typical resistance (Ri), connection on plunger:	10 mOhm

Mechanical data

Total length:	29 mm [1.14 in]
Barrel diameter:	5 mm [.196 in]
Maximum stroke:	5 mm [.196 in]
Spring pre-load:	1 N [3.59 ozf]
Collar height:	1
Spring force at working stroke:	3 N [10.7 ozf]
Recommended working stroke:	4 mm [.157 in]

Test Probe


GKS-364 206 400 N 3001

Item GKS-364-0019



ingun[®]

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 11/25_GB

Learn more about
Test probes

