Exchangeable kit ATS MA09/S-5/ESD

Item 46233-KIT





- Quick, tool-free set-up, can be used without readjustment
- Available in standard, ESD, and RF versions, with or without internal interface
- Modularly configurable signal transmission with internal interfaces
- Pressure plate unit and probe plate unit can be screwed together with stacking screws to form a unit with protected probe field
- Robust, durable design
- Can be customised using functional units for individual configurations
- Detailed accompanying documents (e.g., customising guidelines)



General data

Product group: ATS manual test fixture (MA) Subseries: ATS MAXX ATS MA09 Series: Version: ESD with interface, FR4 Scope of delivery: Unassembled For tandem fixtures: Max. interface signals: Device under test (DUT) side Interface blocks required: Max. internal interface blocks: 5 Internal interface: Available Yes, with compatible additional option Dual-stage contacting: Double-sided contact: Yes, with compatible additional option Weight: 2.75 kg [6.06 lbs] Min. temperature: 10 °C [50 °F] 60 °C [140 °F] Max. temperature: Low voltage: Yes, with suitable additional option RoHS-compliant:

Compatible with

Manual test fixtures (MA): MA x209

Technical data

Pushrod length: 60 mm [2.36 in] Test probe installation height, top: 16 mm [.629 in] Test probe installation height, bottom: 10.5 mm [.413 in] Test probe installation height, dual-stage, bottom: 16 mm [.629 in] Free space above PCB: 58 mm [2.28 in] Useable area (WxD): 150 x 170 mm [5.9 x 6.69 in] Outer dimensionS (WxDxH): 210 x 243 x 203 mm [8.26 x 9.56 x 7.99 in]


EXCHANGEABLE KITS

Exchangeable kit ATS MA09/S-5/ESD

Item 46233-KIT







INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162 78467, Constance, Germany Phone +49 7531 8105-0 Customer hotline +49 7531 8105-888 Fax +49 7531 8105-65 info@ingun.com









Learn more about MA exchangeable kits

