Pre-centering pin

VZ-R-08-40-M-ASYS

Item 116663

GO TO PRODUCT




- Trusted pre-centring for reliable positioning of the PCB fed from the conveyor belt in the inline interchangeable kit
- Suitable for inline interchageable kits WS ASYS/ATH01/173,5 and WS ASYS/ATH01/210,5
- Quick, easy installation on the pressure frame plate

Application

The pre-centring pins (VZ) are installed on the pressure frame plate and are used for the reliable positioning of the PCB fed from the conveyor belt in the inline interchageable kit. They are used in inline interchageable kits WS ASYS/ATH01/173,5 and WS ASYS/ATH01/210,5 and are installed on both sides.

Delivery

Delivery includes 4 pre-centring pins and installation accessories.



General data

Product group: Pre-centering pins Series: VZТуре: Pre-centring pin, round, centric Not ESD compliant Version: Additional function Accessory type: Scope of delivery: 4 pieces including installation accessories 3.3206, anodised Material: Colour: Silver Weight: 0.03 kg [.066 lbs] Min. temperature: 10 °C [50 °F] Max. temperature: 60 °C [140 °F] RoHS-compliant:

Compatible with

Interchangeable kits (WS):

Technical data

Installation: Length: Diameter: WS ASYS/ATH01/...

Thread M4 40 mm [1.57 in] 8 mm [.314 in]


Pre-centering pin

VZ-R-08-40-M-ASYS

Item 116663

O TO PRODUCT





INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162 78467, Constance, Germany Phone +49 7531 8105-0 Customer hotline +49 7531 8105-888 Fax +49 7531 8105-65 info@ingun.com





