







GO TO PRODUCT

- Robust test probes with distinctive collar (stop) on the barrel
- Optimum adjustment of the stroke ratios in the test fixture:  
The collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights
- Stainless steel versions for temperatures from -100 °C up to +200 °C available



1:1



### General data

Product group: ICT / FCT (in-circuit test and function test)  
 Sub-product group: Metric standard  
 Series: GKS-113  
 Grid: 4 mm [157 mil]  
 Contacting from: Pad  
 Magnetic: Yes  
 Installation type: Plug-in  
 Quick-exchange system: Yes  
 Adjustable installation height: No  
 Non-rotating: No  
 Compatible receptacle(s): KS-113  
 Min. temperature: -40 °C [-40 °F]  
 Max. temperature: 80 °C [176 °F]  
 RoHS-compliant: Yes

### Tip style data

Tip style: 04 4-point crown  
 Tip diameter: 1.8 mm [0.07 in]  
 Tip style surface: A gold  
 Tip style material: 2 steel

### Electrical data

Current load capacity / rated current: 5 A  
 Typical resistance (Ri): 30 mOhm

### Mechanical data

Total length: 30.3 mm [1.19 in]  
 Barrel diameter: 2.65 mm [0.104 in]  
 Maximum stroke: 5.3 mm [0.208 in]  
 Spring pre-load: 0.21 N [0.755 ozf]  
 Collar height: 05  
 Spring force at working stroke: 0.6 N [2.15 ozf]  
 Recommended working stroke: 4 mm [0.157 in]

Test Probe

**GKS-113 204 180 A 0605**

Item GKS-113-0019



**ingun**<sup>®</sup>

Partner for Future Technology



**INGUN Prüfmittelbau GmbH**

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 12/25\_GB

Learn more about  
ICT/FCT Test probes



ICT/FCT TEST PROBES

ingun.com