

Receptacle

KS-100 47 05-13

Item KS-1004705-13



GO TO PRODUCT

ingun[®]

Partner for Future Technology

General data

Product group:	Receptacles (KS)
Series:	KS-100
Sub-series:	KS-100 press-in version
Type of receptacle connection:	Wire-wrap
Press ring:	No
Surface area:	Gold
Collar diameter:	1.8 mm [.07 in]
Collar height:	0.2 mm [.007 in]
Wire-wrap post length:	13.2 mm [.519 in]
Knurl:	No
Vacuum-tight:	yes (< 1 ccm / min)
RoHS-compliant:	Yes

Mechanical data

Total length:	41.5 mm [1.63 in]
Outer diameter:	1.67 mm [.065 in]

Mounting hole

Mounting hole in CEM1:	1.68 – 1.69 mm [.066 – .066 in]
Mounting hole in FR4:	1.69 – 1.7 mm [.066 – .066 in]

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 11/25_GB

Learn more about
Test probes



ingun.com

RECEPTACLES