RF absorber mat

HF-A-3,5GHz-ATSMA13/HF/AL

Item 112721





- RF absorber for radio-frequency exchangeable kit for setting up an interference-free, internal radio network
- Reliable prevention of unwanted reflections of radio signals within the radio-frequency chamber

Application


RF absorbers are used to cover the inner walls of the radio-frequency exchangeable kit in order to create an interference-free radio network and prevent reflections of radio signals within the RF chamber. The RF absorber is selected based on the frequency used and the size of the exchangeable kit.

Note:

Refer to the customising guidelines document INFO 4585 to ensure correct installation of the RF absorber.

RF absorbers have a conductive (light grey) and a non-conlight grey side faces the RF DUT and the anthracite side faces the RF chamber.

General data Product group: RF accessories Series: HF-A RF absorber set Type: Version: RF exchangeable kit ATS MA13/HF Accessory type: Customising accessories Scope of delivery: Unassembled Material: RF plastic foam Weight: 0.76 kg [1.67 lbs] 10 °C [50 °F] Min. temperature: Max. temperature: 60 °C [140 °F] RoHS-compliant: Yes



Note:

PCB are reduced.

Compatible with

Exchangeable kits version: HF, ESD MA exchangeable kits (ATS MA): ATS MA13(/S-10)/HF/AL/ESD

Technical data

Free space above PCB: 40 mm [1.57 in] Frequency up to: 3.5 GHz Useable area (WxD): 375 x 230 mm [14.7 x 9.05 in] Outer dimensionS (WxDxH): 445 x 292 x 195 mm [17.5 x 11.4 x 7.67 in]


RF absorber mat

HF-A-3,5GHz-ATSMA13/HF/AL

Item 112721







Radio-frequency exchangeable kits

Part no.	Designation	Version
154013	ATS MA13/HF/AL/ESD	Radio-frequency exchangeable kit without internal interface
154113	ATS MA13/S-10/HF/AL/ESD	Radio-frequency exchangeable kit with internal interface

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162 78467, Constance, Germany Phone +49 7531 8105-0 Customer hotline +49 7531 8105-888 Fax +49 7531 8105-65 info@ingun.com





