

Technical drawing of the FB-LED-D-MAx14 (Pass/fail LED indication) assembly, showing three views: front, side, and perspective.

Front View (A-B): Shows the main assembly with dimensions 606 (total length) and 450 (distance to dimmer). The dimmer is labeled "Dimmer". The cable length is specified as "Kabellänge 1,0 m" (cable length 1.0 m). The mounting bracket is labeled "ISO 14579-A2 M3x10". A detail view shows the mounting bracket dimensions: 15 mm width and 25 mm height.

Side View (C): Shows the side profile of the assembly, highlighting the LED strip and the mounting bracket.

Perspective View (D-E): Shows the assembly from a perspective view, highlighting the LED strip and the mounting bracket.

Notes:

- Bei Verwendung der FB-LED-D-MAx14 (Gut/Schlecht LED-Anzeige) zusammen mit der FB-SIS-BM-MAx14 (Magnetischer Sicherheitsschalter) muss die LED-Lichtleiste auf Maß gekürzt werden (siehe Montagezeichnung).
- The LED light strip has to be cut to size (see installation instructions) when using FB-LED-D-MAx14 (pass/fail LED indication) together with FB-SIS-BM-MAx14 (magnetic safety switch).

Table:

Maßstab/Scale:	1:2	Benennung/Designation:	FB-LED-D-MAx14 Gut/Schlecht LED-Anzeige	
gespeichert/saved:	13.12.2023 09:57:23		FB-LED-D-MAx14 Pass/fail indication	
Montageanleitung/instruction sheet		Artikel-Nr./PartNo.:	115560	Index: 0
ingun				Blatt/Sheet 1 von 1
				DIN A3

RoHS-3;6c