

Detection - present

FB-ABF-A-S-GKS-2

Item 105850




GO TO PRODUCT

ingun[®]

Partner for Future Technology

- Upgrade kits to make operation easier, increase the testing reliability, and to reduce handling times
- Available for manual test fixtures and exchangeable kits
- Wide range of varying functions



General data

Product group:
Series:
Type:
Version:
Accessory type:
Scope of delivery:
Width:
Height:
Min. temperature:
Max. temperature:
RoHS-compliant:

Functional units
FB-ATSMAXx
Detection unit
PC board inserted
Additional function
Switch incl. GKS-114-0015
12 mm [.472 in]
21 mm [.826 in]
10 °C [50 °F]
60 °C [140 °F]
Yes

Compatible with

Manual test fixtures (MA):
Vacuum test fixtures (VA):
MA exchangeable kits (ATS MA):

MA 2012
VA 20xx
ATS MAXx

Technical data

Connection: Solder eyelet
Force: 3 N [10.7 ozf]
Max. current: 1 A
Installation: M3 screw
Max. voltage: 125 V
Length: 13 mm [.511 in]
Outer dimensionS (WxDxH): 12 x 13 x 21 mm [.472 x .511 x .826 in]

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 11/25_GB

Learn more about
MA functional units

