





## Positionstest

Zur Überprüfung der korrekten Position des Kontaktterminals im Steckergehäuse

- Step probes are used to test the correct position of the contact terminals (contact lamellae) in the plug housings. A connection test can be carried out at the same time. Contact will only occur when the tip of the step probe is correctly positioned
- For optimum contacting, various tip styles are available in various tip  $\phi$ , disc  $\phi$  and pin lengths



### General data

|                                 |                                  |
|---------------------------------|----------------------------------|
| Screw-in torque max.:           | 20 cNm [1.77 lbf-in]             |
| Product group:                  | Step probes                      |
| Sub-product group:              | Step probes                      |
| Series:                         | T-113 M screw-in                 |
| Grid:                           | 4 mm [157 mil]                   |
| Contacting from:                | Post                             |
| Magnetic:                       | Yes                              |
| Installation type:              | Screw-in                         |
| Quick-exchange system:          | Yes                              |
| Adjustable installation height: | No                               |
| Non-rotating:                   | No                               |
| Screw-in torque:                | 10 – 20 cNm [.885 – 1.77 lbf-in] |
| Compatible receptacle(s):       | KS-113 M                         |
| Min. temperature:               | -40 °C [-40 °F]                  |
| Max. temperature:               | 80 °C [176 °F]                   |
| RoHS-compliant:                 | Yes                              |

### Tip style data

|                        |                  |
|------------------------|------------------|
| Tip style:             | 02 flat          |
| Tip diameter:          | 1.4 mm [.055 in] |
| Tip style surface:     | A gold           |
| Tip style material:    | 3 CuBe           |
| Step probe tip height: | 2 mm [.078 in]   |
| Disk diameter:         | 3.5 mm [.137 in] |

### Electrical data

|                                        |         |
|----------------------------------------|---------|
| Current load capacity / rated current: | 8 A     |
| Typical resistance (Ri):               | 30 mOhm |

### Mechanical data

|                                 |                   |
|---------------------------------|-------------------|
| Total length:                   | 28.3 mm [1.11 in] |
| Barrel diameter:                | 2.65 mm [.104 in] |
| Maximum stroke:                 | 5 mm [.196 in]    |
| Spring pre-load:                | 0.8 N [2.87 ozf]  |
| Collar height:                  | 02                |
| Spring force at working stroke: | 3 N [10.7 ozf]    |
| Recommended working stroke:     | 4 mm [.157 in]    |

# Test Probe


## T-113 302 140 200 350A3002M

Item T-113-0069



**ingun**<sup>®</sup>

Partner for Future Technology



### INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 12/25\_GB

Learn more about  
Screw-in test probe



ingun.com

SCREW-IN TEST PROBE