

# High-current test probe

## HSS-118 319 200 A 3003

Item HSS-118-0669




GO TO PRODUCT



**ingun**<sup>®</sup>

Partner for Future Technology

- Trusted, robust high-current probes, optimally sized for current load capacity ratio
- Low-Ohm probe with Ri typical: < 10 mOhm
- For use in function and burn-in tests
- Large selection of tip styles and spring forces for optimum contact with DUT
- Optimum adjustment of the stroke ratios in the test fixture: The test probe collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights



1:1



### General data

|                                 |                         |
|---------------------------------|-------------------------|
| Product group:                  | Standard HSS (press-in) |
| Sub-product group:              | Standard HSS (press-in) |
| Series:                         | HSS-118                 |
| Grid:                           | 2.54 mm [100 mil]       |
| Contacting from:                | Post                    |
| Magnetic:                       | Yes                     |
| Installation type:              | Plug-in                 |
| Quick-exchange system:          | Yes                     |
| Adjustable installation height: | No                      |
| Non-rotating:                   | No                      |
| Compatible receptacle(s):       | KS-112                  |
| Min. temperature:               | -100 °C [-148 °F]       |
| Max. temperature:               | 200 °C [392 °F]         |
| RoHS-compliant:                 | Yes                     |

### Tip style data

|                     |                                             |
|---------------------|---------------------------------------------|
| Tip style:          | 19 90° inverse cone, slotted, self cleaning |
| Tip diameter:       | 2 mm [0.078 in]                             |
| Tip style surface:  | A gold                                      |
| Tip style material: | 3 CuBe                                      |

### Electrical data

|                                        |         |
|----------------------------------------|---------|
| Current load capacity / rated current: | 20 A    |
| Typical resistance (Ri):               | 10 mOhm |

### Mechanical data

|                                 |                    |
|---------------------------------|--------------------|
| Total length:                   | 32.3 mm [1.27 in]  |
| Barrel diameter:                | 1.66 mm [0.065 in] |
| Maximum stroke:                 | 5.3 mm [0.208 in]  |
| Spring pre-load:                | 1 N [3.59 ozf]     |
| Collar height:                  | 3                  |
| Spring force at working stroke: | 3 N [10.7 ozf]     |
| Recommended working stroke:     | 4 mm [0.157 in]    |

# High-current test probe


## HSS-118 319 200 A 3003

Item HSS-118-0669



**ingun**<sup>®</sup>

Partner for Future Technology



### INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 11/25\_GB

Learn more about  
High-current test probes



ingun.com

HIGH-CURRENT TEST PROBES