

This technical documentation is intellectual property of INGUN Prüfmittelbau GmbH. Unless otherwise contractually agreed in writing, it is not permitted to duplicate or disseminate it, nor may it be made accessible to third parties in any other way, or otherwise be misused without our explicit prior consent.

Diese technische Unterlage ist geistiges Eigentum der Fa. INGUN Prüfmittelbau GmbH. Sofern keine anderslautende schriftliche vertragliche Regelung besteht, darf sie ohne ausdrückliche vorherige Einwilligung weder vervielfältigt, noch verbreitet, noch dritten Personen in sonstiger Weise zugänglich gemacht werden, noch anderweitig missbraucht werden.

	1	2	3	4	5	6	7	8
A								Technische Daten: Maximaler Arbeitshub: 2,0 mm Empfohlener Arbeitshub: 1,5 mm Anpresskraft bei Arbeitshub: 3N Markierfläche: Kreis 2mm ø Empfohlener Markierimpuls: ca. 1 sec. Stichelmaterial: Vollhartmetall Außengewinde: M12x1 Außenabmaße (dxl): ø12 x 60 mm Getriebemotor Daten: Nennspannung: =12 V Typenleistung: 0,75 W Leerlaufstrom: 3,68 mA Anlaufstrom: 106 mA Anschlusswiderstand: 114 Ohm Max. Dauerbelastungsstrom: 81,0 mA Stichelleerlaufdrehzahl: 3,0 sec. -1 Max. Stichelndrehmoment: 54 mNm
B								
C	Technical drawing of the marking unit showing front and side views with dimensions. Front view dimensions: $\phi 6$, $\phi 2$, SW14, SW10,9. Side view dimensions: Markierradius 1mm, 2,5, 9,3, M12x1, (59,8).							Technical Data: Maximum working stroke: 2,0 mm Recommended working stroke: 1,5 mm Spring Force (at recommended working stroke): 3N Marking area: Circle ø2mm Recommended marking impulse: ca. 1 sec. Engraver material: hard metall External thread: M12x1 Overall Dimensions (dxl): ø12 x 60 mm Geared Motor Data: Rated voltage: =12 V Performance: 0,75 W Idle current: 3,68 mA Start-up current: 106 mA Connection resistance: 114 Ohm Max. permanent load current: 81,0 mA Engraver idle running speed: 3,0 sec. -1 Max. Engraver torque: 54 mNm
D								
E								3D perspective view of the marking unit.
F								

Maßstab/Scale: 2:1

gespeichert/saved: 19.03.2015 08:42:34

Montageanleitung/instruction sheet

Benennung/Designation:

ME-E-S2.0-12-060-K12V Markiereinheit
ME-E-S2.0-12-060-K12V | Marking Unit

Artikel-Nr./PartNo.: 25251

Index: 0

Blatt/Sheet 1 von 1
DIN A3

RoHS