






GO TO PRODUCT

- Well-established test probes for contacting PCBs



1:1



General data

| | |
|---------------------------------|---|
| Product group: | ICT / FCT (in-circuit test and function test) |
| Sub-product group: | Standard stroke test probe |
| Series: | GKS-100 LH long version |
| Grid: | 3 mm [118 mil] |
| Contacting from: | Post |
| Magnetic: | Yes |
| Installation type: | Plug-in |
| Quick-exchange system: | Yes |
| Adjustable installation height: | No |
| Non-rotating: | No |
| Compatible receptacle(s): | KS-100 |
| Min. temperature: | -40 °C [-40 °F] |
| Max. temperature: | 80 °C [176 °F] |
| RoHS-compliant: | Yes |

Tip style data

| | |
|---------------------|------------------|
| Tip style: | 06 serrated |
| Tip diameter: | 2.5 mm [.098 in] |
| Tip style surface: | A gold |
| Tip style material: | 3 CuBe |

Electrical data

| | |
|--|---------|
| Current load capacity / rated current: | 5 A |
| Typical resistance (Ri): | 20 mOhm |

Mechanical data

| | |
|---------------------------------|-------------------|
| Total length: | 35.4 mm [1.39 in] |
| Barrel diameter: | 1.37 mm [.053 in] |
| Maximum stroke: | 6.35 mm [.25 in] |
| Spring pre-load: | 0.2 N [.719 ozf] |
| Collar height: | 00 |
| Spring force at working stroke: | 0.6 N [2.15 ozf] |
| Recommended working stroke: | 4.3 mm [1.69 in] |

Test Probe


GKS-100 306 250 A 0600 LH

Item GKS-100-1772



ingun[®]

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 01/26_GB

Learn more about
ICT/FCT Test probes



ingun.com