





GO TO PRODUCT

- Well-established test probes for contacting PCBs
- For optimal contact to the test points (e.g. pads, vias, and pins), various tip styles with various diameters and finishes are available.
- Various spring forces available as well as versions with stainless steel springs suitable for high temperatures
- Used for setting the optimum stroke conditions in the test fixture, various installation heights can be achieved by combining test probes and receptacles



### General data

|                                 |                                               |
|---------------------------------|-----------------------------------------------|
| Product group:                  | ICT / FCT (in-circuit test and function test) |
| Sub-product group:              | Standard stroke test probe                    |
| Series:                         | GKS-100                                       |
| Grid:                           | 2.54 mm [100 mil]                             |
| Contacting from:                | Pad                                           |
| Magnetic:                       | Yes                                           |
| Installation type:              | Plug-in                                       |
| Quick-exchange system:          | Yes                                           |
| Adjustable installation height: | No                                            |
| Non-rotating:                   | No                                            |
| Compatible receptacle(s):       | KS-100                                        |
| Min. temperature:               | -40 °C [-40 °F]                               |
| Max. temperature:               | 80 °C [176 °F]                                |
| RoHS-compliant:                 | Yes                                           |

### Tip style data

|                     |                               |
|---------------------|-------------------------------|
| Tip style:          | 05 bullet-nosed (full radius) |
| Tip diameter:       | 0.64 mm [0.025 in]            |
| Tip style surface:  | A gold                        |
| Tip style material: | 3 CuBe                        |

### Electrical data

|                                        |         |
|----------------------------------------|---------|
| Current load capacity / rated current: | 8 A     |
| Typical resistance (Ri):               | 20 mOhm |

### Mechanical data

|                                 |                    |
|---------------------------------|--------------------|
| Total length:                   | 33.4 mm [1.31 in]  |
| Barrel diameter:                | 1.37 mm [0.053 in] |
| Maximum stroke:                 | 6.35 mm [0.25 in]  |
| Spring pre-load:                | 0.78 N [2.8 ozf]   |
| Collar height:                  | 0                  |
| Spring force at working stroke: | 3 N [10.7 ozf]     |
| Recommended working stroke:     | 4.3 mm [0.169 in]  |

# Test Probe

## GKS-100 305 064 A 3000

Item GKS-100-0136



**ingun**<sup>®</sup>

Partner for Future Technology



### INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 11/25\_GB

Learn more about  
ICT/FCT Test probes



ICT/FCT TEST PROBES

ingun.com