Connector - plug pole clamp STV-PK4-M4-SW

Item 3645





- Pole terminal with claw edge, captive insulating head and insulating rings
- Threaded bolt with 4 mm diameter made of nickel-plated brass, with 2 mm diameter cross hole

Application

For insulated, non-rotating installation in the interface block and in device frame and control panels up to 2 mm wall thickness.







General data

Product group:

Series:

Type:

Version: Accessory type:

Component assembly:

Material:


Colour:

Weight:

Min. temperature:

Max. temperature:

RoHS-compliant:



Compatible with

Interface blocks (SB):

Technical data

Connection:

Electric accessory

Socket D4, radial bore D2

Customising accessories

Brass, nickel-plated

0.01 kg [.022 lbs]

-25 °C [-13 °F]

100 °C [212 °F]

STV Pole clamp

Black

Max. current: Installation:

Max. voltage:

Number of poles:

Length:

Diameter:

M4 threaded connection 35 A Thread M4 30 VAC / 60 VDC 41.5 mm [1.63 in] 4 mm [.157 in]

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162 78467, Constance, Germany Phone +49 7531 8105-0 Customer hotline +49 7531 8105-888 Fax +49 7531 8105-65 info@ingun.com







