







- Extremely robust test probes for applications with unwanted side and axial forces
- For use in applications with limited space



General data

Product group:	Assorted test probes
Sub-product group:	Short stroke GKS / charge and transfer GKS
Series:	GKS-365
Grid:	6.5 mm [255 mil]
Contacting from:	Pad
Magnetic:	Yes
Installation type:	Plug-in
Quick-exchange system:	Yes
Adjustable installation height:	No
Non-rotating:	No
Compatible receptacle(s):	KS-365
Min. temperature:	-40 °C [-40 °F]
Max. temperature:	80 °C [176 °F]
RoHS-compliant:	Yes

Tip style data

Tip style:	13 30° needle tip, rounded
Tip diameter:	4 mm [.157 in]
Tip style surface:	N nickel
Tip style material:	1 brass

Electrical data

Current load capacity / rated current:	5 A
Typical resistance (Ri):	30 mOhm

Mechanical data

Total length:	15 mm [.59 in]
Barrel diameter:	4.97 mm [.195 in]
Maximum stroke:	4 mm [.157 in]
Spring pre-load:	0.5 N [1.79 ozf]
Collar height:	01
Spring force at working stroke:	1.5 N [5.39 ozf]
Recommended working stroke:	3.2 mm [.125 in]

Test Probe


GKS-365 113 400 N 1501

Item GKS-365-0014



ingun[®]

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 12/25_GB

Learn more about
Test probes

