# FB-VER-F-M-RC

## FB-VER-F-M-RC

Item 116130






- Secure hold of the test fixture on the base plate of the Pylon
- Protection against lifting of the front of the test fixture during locking
- The test fixture must be equipped with the fixture fixing mechanism.

#### **Application**

The functional unit is used to securely fix the test fixture to the base plate of the Pylon receiver and serves as protection against the front of the test fixture lifting while locked.



#### **General data**

Product group: Locking units Series: FB-RC Receiver/test fixture fixing mechanism Type: Version: RECEIVER

Accessory type: Additional function Scope of delivery: Must be installed upon delivery, installation

accessories included

Material: 1.2842 Width: 15 mm [.59 in] Height: 3.3 mm [.129 in] Weight: 0.04 kg [.088 lbs] Min. temperature: 10 °C [50 °F] 60 °C [140 °F] Max. temperature: RoHS-compliant: Yes

#### **Compatible with**

Accessories: Pylon-WSO-ASYS

### **Technical data**

Installation: Thread M4 Length: 50 mm [1.96 in] Outer dimensionS (WxDxH): 50 x 15 x 3.3 mm [1.96 x .59 x .129 in]


# FB-VER-F-M-RC


# FB-VER-F-M-RC

Item 116130









#### **Accessories**

Part no.	Designation	Version
116150	FB-VER-F-M-MA/VA	Fixation test fixture

INGUN Prüfmittelbau GmbH Max-Stromeyer-Straße 162 78467, Constance, Germany Phone +49 7531 8105-0 Customer hotline +49 7531 8105-888 Fax +49 7531 8105-65 info@ingun.com









Learn more about Test fixture kits

