




GO TO PRODUCT



General data

Product group:	ICT / FCT (in-circuit test and function test)
Sub-product group:	INGUN E-TYPE®
Series:	E-035
Grid:	1.91 mm [75.1 mil]
Contacting from:	Pad
Magnetic:	Yes
Installation type:	Plug-in
Quick-exchange system:	Yes
Adjustable installation height:	No
Non-rotating:	No
Compatible receptacle(s):	KS-075
Min. temperature:	-40 °C [-40 °F]
Max. temperature:	80 °C [176 °F]
RoHS-compliant:	Yes

Tip style data

Tip style:	70 asymmetric slanted needle tip
Tip diameter:	0.2 mm [.007 in]
Tip style surface:	E palladium / nickel
Tip style material:	2 steel

Electrical data

Current load capacity / rated current:	3 A
Typical resistance (Ri):	20 mOhm

Mechanical data

Total length:	36.8 mm [1.44 in]
Barrel diameter:	1.02 mm [.04 in]
Maximum stroke:	10 mm [.393 in]
Spring pre-load:	0.59 N [2.12 ozf]
Collar height:	0
Spring force at working stroke:	1.2 N [4.31 ozf]
Recommended working stroke:	8 mm [.314 in]

Test Probe INGUN E-Type


E-035 270 026 E 1200

Item E-035-0002



ingun[®]

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 11/25_GB

Learn more about
ICT/FCT Test probes



ICT/FCT TEST PROBES

ingun.com