

# Vacuum test fixture

## VA 4060/D/H/VPC-G12

Item 114666



GO TO PRODUCT

**ingun**<sup>®</sup>

Partner for Future Technology

- Vacuum test fixture with parallel lifting vacuum cassette
- Robust, maintenance-friendly design with outstanding service life
- Increased ease of use thanks to simple, intuitive handling
- Easy access to housing interior thanks to wide opening angle
- Vacuum cassette can be upgraded for dual-stage contacting
- For the assembly of items delivered unassembled, Refer to the drawings of the items specified in the parts list to assemble items

NEW



### Application

Typical service life of tip is approximately 25,000 load cycles (laboratory conditions)

### Version

- 10 mm thick, deflection-resistant probe plate (KTP) made of FR4
- Incl. 6 mm thick moving plate (ADP) with ESD-conductive surface, including 4 captive screws
- Tool-free access to the probe plate (KTP) to replace worn test probes easily
- Housing to be opened with tool (TORX T20)
- Foldable bow handles for safe, easy transport.

### Note:

The customising guidelines document INFO 4630 should be referred to for the professional customisation of VA 40xx test fixtures for single-stage contacting. For dual-stage contacting customisation, please refer to customising guidelines document INFO 4638.

### Delivery

The product is delivered partially assembled. The housing is fully assembled. The vacuum cassette with components to be reworked for a DUT-specific customisation must be assembled upon delivery.

### General data

|                                  |                          |
|----------------------------------|--------------------------|
| Test system interface:           | VPC-G12                  |
| Product group:                   | Vacuum test fixture (VA) |
| Main series:                     | VA xxxx                  |
| Subseries:                       | VA 40xx                  |
| Series:                          | VA 4060                  |
| Size:                            | xx60                     |
| Test fixture type:               | Stand-alone test fixture |
| Contact stroke generation:       | Vacuum                   |
| Housing type:                    | Desk housing             |
| Contacting direction:            | 1-stage / 2-stage        |
| Max. contact force:              | 23,000 N [82,729 ozf]    |
| Approx. parallel contact stroke: | 12.8 mm [.503 in]        |
| Weight:                          | 16.3 kg [35.9 lbs]       |
| Min. temperature:                | 10 °C [50 °F]            |
| Max. temperature:                | 60 °C [140 °F]           |
| RoHS-compliant:                  | Yes                      |

### Technical data

|                                                     |                                               |
|-----------------------------------------------------|-----------------------------------------------|
| Test probe installation height, bottom:             | 16 mm [.629 in]                               |
| Test probe installation height, dual-stage, bottom: | 21.3 mm [.838 in]                             |
| Force of gas pressure springs:                      | 400 N (L: 200 N / R: 200 N)                   |
| Standard version:                                   | Yes                                           |
| Useable area, standard (WxD):                       | 550 x 430 mm [21.6 x 16.9 in]                 |
| ESD version:                                        | No                                            |
| Radio frequency version:                            | No                                            |
| Rigid pin version:                                  | No                                            |
| Dual-stage version:                                 | <p>Yes, with compatible additional option</p> |
| Useable area, dual-stage (WxD):                     | 530 x 430 mm [20.8 x 16.9 in]                 |
| Additional contacting unit (ZSK), top:              | Yes, with suitable additional option          |
| Outer dimensions, closed (WxDxH):                   | 675 x 600 x 176 mm [26.5 x 23.6 x 6.92 in]    |

# Vacuum test fixture VA 4060/D/H/VPC-G12


Item 114666




GO TO PRODUCT

**ingun**<sup>®</sup>

Partner for Future Technology



## Housing perforations and pilot holes



Perforated for:

- 1. Cable connections
- 2. Additional handles
- 4. Stroke counter

Prepared for:

- 3. ESD discharge button
- 5. Anti-pinch protection
- 6. Alum-A handles
- 7. Earthing contact

## Accessories

| Part no. | Designation             | Version                                            |
|----------|-------------------------|----------------------------------------------------|
| 114716   | FB-2VE-VA4060           | Dual-stage shifting unit                           |
| 107216   | VD-V-4060-2             | Vakuumdichtung außen                               |
| 107048   | VD-Z-21-300-200-2       | Vacuum seal vacuum-free zone (fixed dimensions)    |
| 109501   | VD-Z-21-XXX-XXX-2       | Vacuum seal vacuum-free zone (variable dimensions) |
| 8078     | GDF-305-120-200N-A6-A6  | Gas pressure spring                                |
| 105791   | FED-10,0-24,5-103N-11,6 | Pressure spring                                    |
| 2599     | HBS-03,0-10,0           | Stroke-limiting disk                               |
| 116613   | EHZ-08-R-11-TR          | Electric stroke counter                            |
| 113481   | FB-TWA                  | Alum-A transport bracket                           |
| 17036    | FB-ALS-VAxxxx-2S        | ESD discharge probe                                |
| 115944   | MAP VA4060              | Ground plate                                       |

## INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 11/25\_GB

Learn more about  
Test fixture kits

