Stroke-limiting disk

HBS-05,0-07,0

Item 11890





- Defined height stop for ICT and/or combined ICT/FCT contacting
- Reliable parallel contact stroke thanks to ideally matched stroke limitation
- · Quick, easy installation

Application

Stroke-limiting disks are used as height stops in vacuum test fixtures for reliable regulation of the parallel contact stroke in ICT and/or combined ICT/FCT contacting.





Ø6.1[.240]	Ø7[.276]
1.5[.059]	_
6.5[.256]	_

General data

Product group: Stroke-limiting disk / stroke-limiting pin Series: HBS Type: Stroke limitation Version: VA xxxx (2-stage) Accessory type: Customising accessories Material: Delrin

 $\begin{array}{lll} \text{Material:} & \text{Delrin} \\ \text{Colour:} & \text{White} \\ \text{Height:} & 6.5 \text{ mm } \text{[.255 in]} \\ \text{Min. temperature:} & 10 \, ^{\circ}\text{C } \text{[50 }^{\circ}\text{F]} \\ \text{Max. temperature:} & 60 \, ^{\circ}\text{C } \text{[140 }^{\circ}\text{F]} \\ \text{RoHS-compliant:} & \text{Yes} \\ \end{array}$

Compatible with

Vacuum test fixtures (VA): VA3070
For dual-stage contacting: Yes

Technical data

 Tip height:
 5 mm [.196 in]

 Diameter:
 7 mm [.275 in]

 Pin diameter:
 6.1 mm [.24 in]

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162 78467, Constance, Germany Phone +49 7531 8105-0 Customer hotline +49 7531 8105-888 Fax +49 7531 8105-65 info@ingun.com







