High-current test probe

HSS-120 355 300 A 1502


Item HSS-120-0130






- Trusted, robust high-current probes, optimally sized for current load capacity ratio
- Low-Ohm probe with Ri typical: < 10 mOhm
- For use in function and burn-in tests
- Large selection of tip styles and spring forces for optimum contact with DUT
- Optimum adjustment of the stroke ratios in the test fixture: The test probe collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights











General data

RoHS-compliant:

Standard HSS (press-in) Product group: Sub-product group: Standard HSS (press-in) HSS-120 Series: 4 mm [157 mil] Contacting from: Pad Magnetic: Yes Installation type: Plug-in Quick-exchange system: Yes Adjustable installation height: No Non-rotating: No Compatible receptacle(s): KS-113 -100 °C [-148 °F] Min. temperature: Max. temperature: 200 °C [392 °F]

Tip style data

Tip style: 55 bullet-nosed, special length Tip diameter: 3 mm [.118 in] Tip style surface: A gold Tip style material: 3 CuBe

Electrical data

Current load capacity / rated current: 30 A Typical resistance (Ri): 10 mOhm

Mechanical data

Total length: 29.3 mm [1.15 in] Barrel diameter: 2.65 mm [.104 in] Maximum stroke: 5.3 mm [.208 in] 0.45 N [1.61 ozf] Spring pre-load: Collar height: 1.5 N [5.39 ozf] Spring force at working stroke: 4 mm [.157 in] Recommended working stroke:

HIGH-CURRENT TEST PROBES

High-current test probe HSS-120 355 300 A 1502

Item HSS-120-0130







INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162 78467, Constance, Germany Phone +49 7531 8105-0 Customer hotline +49 7531 8105-888 Fax +49 7531 8105-65 info@ingun.com







Learn more about **High-current test probes**

