


Durchgangsprüfung

Zur Überprüfung von möglichen offenen Verbindungen, Kurzschlüssen und Fehlverdrahtungen



General data

Product group:
Sub-product group:
Series:
Grid:
Contacting from:
Magnetic:
Installation type:
Quick-exchange system:
Adjustable installation height:
Non-rotating:
Compatible receptacle(s):
Min. temperature:
Max. temperature:
RoHS-compliant:

Screw-in test probe
Non-rotating test probes
GKS-098
4 mm [157 mil]
Female connector
Yes
Plug-in
Yes
No
Yes
KS-103 23
-40 °C [-40 °F]
80 °C [176 °F]
Yes

Tip style data

Tip style:
Tip diameter:
Tip style surface:
Tip style material:
Spade width:
Spade length:

29 spade, flat with flat head
3 mm [.118 in]
R rhodium
3 CuBe
0.7 mm [.027 in]
6.5 mm [.255 in]

Electrical data

Current load capacity / rated current:
Typical resistance (Ri):

10 A
30 mOhm

Mechanical data

Total length:
Barrel diameter:
Maximum stroke:
Spring pre-load:
Collar height:
Spring force at working stroke:
Recommended working stroke:

28.6 mm [1.12 in]
3 mm [.118 in]
5 mm [.196 in]
0.45 N [1.61 ozf]
07
1.5 N [5.39 ozf]
4 mm [.157 in]

Test Probe


GKS-098 329 300 R 1507

Item GKS-098-0001



ingun[®]

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 11/25_GB

Learn more about
Screw-in test probe



SCREW-IN TEST PROBE

ingun.com