

Receptacle

KS-112 30 G8


Item KS-11230G8




GO TO PRODUCT

ingun[®]

Partner for Future Technology



1:1



General data

Product group:
Series:
Sub-series:
Type of receptacle connection:
Press ring:
Surface area:
Collar diameter:
Collar height:
Knurl:
Vacuum-tight:
RoHS-compliant:

Receptacles (KS)
KS-112
KS-112 press-in version
Solder
Yes
Gold
2.08 mm [.081 in]
8 mm [.314 in]
No
No
Yes

Mechanical data

Total length: 30 mm [1.18 in]
Outer diameter: 2 mm [.078 in]

Mounting hole

Mounting hole in CEM1: 1.98 – 2 mm [.077 – .078 in]
Mounting hole in FR4: 1.99 – 2.01 mm [.078 – .079 in]
Mounting hole with press ring in CEM1: 2.03 – 2.05 mm [.079 – .08 in]
Mounting hole with press ring in FR4: 2.03 – 2.05 mm [.079 – .08 in]

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 12/25_GB

Learn more about
Test probes



ingun.com

RECEPTACLES