

# High-current test probe

## HSS-118 306 180 A 3007

Item HSS-118-0638



GO TO PRODUCT




**ingun**<sup>®</sup>

Partner for Future Technology

- Trusted, robust high-current probes, optimally sized for current load capacity ratio
- Low-Ohm probe with Ri typical: < 10 mOhm
- For use in function and burn-in tests
- Large selection of tip styles and spring forces for optimum contact with DUT
- Optimum adjustment of the stroke ratios in the test fixture: The test probe collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights



1:1



### General data

Product group: Standard HSS (press-in)  
 Sub-product group: Standard HSS (press-in)  
 Series: HSS-118  
 Grid: 2.54 mm [100 mil]  
 Contacting from: Post  
 Magnetic: Yes  
 Installation type: Plug-in  
 Quick-exchange system: Yes  
 Adjustable installation height: No  
 Non-rotating: No  
 Compatible receptacle(s): KS-112  
 Min. temperature: -100 °C [-148 °F]  
 Max. temperature: 200 °C [392 °F]  
 RoHS-compliant: Yes

Standard HSS (press-in)  
 Standard HSS (press-in)  
 HSS-118  
 2.54 mm [100 mil]  
 Post  
 Yes  
 Plug-in  
 Yes  
 No  
 No  
 KS-112  
 -100 °C [-148 °F]  
 200 °C [392 °F]  
 Yes

### Tip style data

Tip style: 06 serrated  
 Tip diameter: 1.8 mm [0.07 in]  
 Tip style surface: A gold  
 Tip style material: 3 CuBe

### Electrical data

Current load capacity / rated current: 20 A  
 Typical resistance (Ri): 10 mOhm

### Mechanical data

Total length: 37.3 mm [1.46 in]  
 Barrel diameter: 1.66 mm [0.065 in]  
 Maximum stroke: 5.3 mm [0.208 in]  
 Spring pre-load: 1 N [3.59 ozf]  
 Collar height: 7  
 Spring force at working stroke: 3 N [10.7 ozf]  
 Recommended working stroke: 4 mm [0.157 in]

HIGH-CURRENT TEST PROBES

# High-current test probe


## HSS-118 306 180 A 3007

Item HSS-118-0638



**ingun**<sup>®</sup>

Partner for Future Technology



### INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 11/25\_GB

Learn more about  
High-current test probes



ingun.com

HIGH-CURRENT TEST PROBES