

pressure spring

FED-04,7-14,0-20N-07,5

Item 19994



GO TO PRODUCT

ingun[®]

Partner for Future Technology



- Bewährte, rechts gewickelte, Druckfeder
- Highest spring steel quality for maximum breakage resistance
- Gleichbleibende, konstante Steigung
- Lineare Federkennlinie

Application


Federn (FED) werden als Druckelement verwendet, um die Andruckplatte mit dem Prüfling, nach der Kontaktierung auf das Ursprungsniveau zurück zu heben. Sie werden typischerweise auf der Kontaktträgerplatte montiert.



1:1



$F_n = \sim 19 \text{ N}$ [68.3 ozf]



General data

Product group:

Series:

Type:

Version:

Accessory type:

Material:

Height:

Weight:

Min. temperature:

Max. temperature:

RoHS-compliant:

Pressure springs

FED

Pressure spring

Customising accessories

EN 10270-1-DH

14 mm [.551 in]

0.01 kg [.022 lbs]

10 °C [50 °F]

60 °C [140 °F]

Yes

Compatible with

Accessories:

MBE-FA-SAM-H

Technical data

Force:

Length:

Diameter:

20 N [71.9 ozf]

7.5 mm [.295 in]

4.63 mm [.182 in]

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162

78467, Constance, Germany

Phone +49 7531 8105-0

Customer hotline +49 7531 8105-888

Fax +49 7531 8105-65

info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 11/25_GB