




GO TO PRODUCT

- Plug or cable assemblies for RF test probes (HFS)



General data

Product group:

Series:

Sub-series:

Min. temperature:

Max. temperature:

RoHS-compliant:

Assemblies

SE-RG178

SE-RG178 plug

-55 °C [-67 °F]

135 °C [275 °F]

Yes

Cable data

Cable length:

750 mm [29.5 in]

Cable type:

Kink protection cable:

Shrink-on sleeve, black, 20 mm

Attenuation Fmax:

1 dB

Connector data

Interface 1:

SE-110 plug connector for HFS-110

Interface gender 1:

M signal conductor male / plug

Version 1:

Straight

Interface 2:

Open cable end

Electrical data

Maximum frequency:

.7 GHz

Impedance:

50 Ohm

Cable shielding:

Simple

Maximum performance:

71 W

Performance coefficient:

59 RG178

Dielectric strength:

1 kV

Attenuation coefficient a:

1,40800 RG178

Attenuation coefficient b:

0,22960 RG178

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162

78467, Constance, Germany

Phone +49 7531 8105-0

Customer hotline +49 7531 8105-888

Fax +49 7531 8105-65

info@ingun.com

