




Positionstest

Zur Überprüfung der korrekten Position des Kontaktterminals im Steckergehäuse

NEW



General data

Screw-in torque max.:
Product group:
Sub-product group:
Series:
Grid:
Contacting from:
Magnetic:
Installation type:
Quick-exchange system:
Adjustable installation height:
Non-rotating:
Screw-in torque:
Compatible receptacle(s):
Min. temperature:
Max. temperature:
RoHS-compliant:

1 cNm [.088 lbf·in]
Step probes
Step probes
T-075
1.91 mm [75.1 mil]
Pad
Yes
Screw-in
Yes
No
No
.5 – 1 cNm [.044 – .088 lbf·in]
KS-075 M
-40 °C [-40 °F]
80 °C [176 °F]
Yes

Tip style data

Tip style:
Tip diameter:
Tip style surface:
Tip style material:
Step probe tip height:
Disk diameter:

05 bullet-nosed (full radius)
0.4 mm [.015 in]
A gold
3 CuBe
6 mm [.236 in]
1 mm [.039 in]

Electrical data

Current load capacity / rated current:
Typical resistance (Ri):

3 A
20 mOhm

Mechanical data

Total length:
Barrel diameter:
Maximum stroke:
Spring pre-load:
Collar height:
Spring force at working stroke:
Recommended working stroke:

41.1 mm [1.61 in]
1 mm [.039 in]
6.35 mm [.25 in]
0.24 N [.863 ozf]
02
0.6 N [2.15 ozf]
4.3 mm [.169 in]

Test Probe


T-075 305 040 600 100A0602M

Item T-075-0025



ingun[®]

Partner for Future Technology



INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 12/25_GB

Learn more about
Screw-in test probe



SCREW-IN TEST PROBE

ingun.com