

Receptacle

KS-050 E08

Item KS-050E08




GO TO PRODUCT

ingun[®]

Partner for Future Technology



1:1



General data

Product group:
Series:
Sub-series:
Type of receptacle connection:
Press ring:
Surface area:
Collar diameter:
Collar height:
Knurl:
Vacuum-tight:
RoHS-compliant:

Receptacles (KS)
KS-050
KS-050 press-in version
Plug / open
Yes
Gold
1.04 mm [.04 in]
7.9 mm [.311 in]
No
No
Yes

Mechanical data

Total length: 40.6 mm [1.59 in]
Outer diameter: 0.95 mm [.037 in]

Mounting hole

Mounting hole in CEM1: 0.98 – 1 mm [.038 – .039 in]
Mounting hole in FR4: 0.98 – 1 mm [.038 – .039 in]
Mounting hole with press ring in CEM1: 0.98 – 1 mm [.038 – .039 in]
Mounting hole with press ring in FR4: 0.98 – 1 mm [.038 – .039 in]

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 11/25_GB

Learn more about
Test probes



ingun.com

RECEPTACLES