EXCHANGEABLE KITS

Exchangeable kit


ATS MA13/S-10/KONRAD

Item 59640





- Quick, tool-free set-up, can be used without readjustment
- Available in standard, ESD, and RF versions, with or without internal interface
- Modularly configurable signal transmission with internal interfaces
- Pressure plate unit and probe plate unit can be screwed together with stacking screws to form a unit with protected probe field
- Robust, durable design
- Can be customised using functional units for individual configurations
- Detailed accompanying documents (e.g., customising guidelines)



General data

Product group: ATS manual test fixture (MA) Subseries: ATS MAXX Series: ATS MA13 Version: With interface, KONRAD Scope of delivery: Assembled Max. interface signals: 1700 Interface blocks required: Device under test (DUT) side Max. internal interface blocks: 10 Internal interface: Available Min. temperature: 10 °C [50 °F] Max. temperature: 60 °C [140 °F] RoHS-compliant:

Compatible with

Test systems: KONRAD LEON TINY

Technical data

Pushrod length: 60 mm [2.36 in] Test probe installation height, top: 16 mm [.629 in] Test probe installation height, bottom: 10.5 mm [.413 in] Test probe installation height, dual-stage, bottom: 16 mm [.629 in] Free space above PCB: 58 mm [2.28 in] Useable area (WxD): 440 x 310 mm [17.3 x 12.2 in] Outer dimensionS (WxDxH): 506 x 383 x 202 mm [19.9 x 15 x 7.95 in]


EXCHANGEABLE KITS

Exchangeable kit **ATS MA13/S-10/KONRAD**

Item 59640







INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162 78467, Constance, Germany Phone +49 7531 8105-0 Customer hotline +49 7531 8105-888 Fax +49 7531 8105-65 info@ingun.com









Learn more about MA exchangeable kits

