

# High-current test probe

## HSS-118 303 200 A 3010

Item HSS-118-0605





GO TO PRODUCT


**ingun**<sup>®</sup>

Partner for Future Technology

- Trusted, robust high-current probes, optimally sized for current load capacity ratio
- Low-Ohm probe with Ri typical: < 10 mOhm
- For use in function and burn-in tests
- Large selection of tip styles and spring forces for optimum contact with DUT
- Optimum adjustment of the stroke ratios in the test fixture: The test probe collar is available in different heights, which, in combination with the receptacles, allows a range of installation heights



1:1



### General data

Product group:  
Sub-product group:  
Series:  
Grid:  
Contacting from:  
Magnetic:  
Installation type:  
Quick-exchange system:  
Adjustable installation height:  
Non-rotating:  
Compatible receptacle(s):  
Min. temperature:  
Max. temperature:  
RoHS-compliant:

Standard HSS (press-in)  
Standard HSS (press-in)  
HSS-118  
2.54 mm [100 mil]  
Post  
Yes  
Plug-in  
Yes  
No  
No  
KS-112  
-100 °C [-148 °F]  
200 °C [392 °F]  
Yes

### Tip style data

Tip style:  
Tip diameter:  
Tip style surface:  
Tip style material:

03 inverse cone  
2 mm [0.078 in]  
A gold  
3 CuBe

### Electrical data

Current load capacity / rated current:  
Typical resistance (Ri):

20 A  
10 mOhm

### Mechanical data

Total length:  
Barrel diameter:  
Maximum stroke:  
Spring pre-load:  
Collar height:  
Spring force at working stroke:  
Recommended working stroke:

40.3 mm [1.58 in]  
1.66 mm [0.065 in]  
5.3 mm [0.208 in]  
1 N [3.59 ozf]  
10  
3 N [10.7 ozf]  
4 mm [0.157 in]

HIGH-CURRENT TEST PROBES


# High-current test probe HSS-118 303 200 A 3010

Item HSS-118-0605



**ingun**<sup>®</sup>

Partner for Future Technology



## INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 11/25\_GB

Learn more about  
High-current test probes



ingun.com

HIGH-CURRENT TEST PROBES