SOFT-SHIELD RF seal

HF-D-SSD-RWP-ATSMA13/14/HF

Item 32918






- Spare parts kit for quick, reliable and preventive maintenance
- Easy exchange on site

Application

Spare parts are required as part of preventive maintenance or as soon as components wear out during normal operation and need to be replaced. The RF seals are inserted into the grooves provided for this purpose. The grooves must be degreased before fitting the seal. We recommend wearing gloves when replacing the RF seals.



Note:

The RF seals have a typical service life of approximately 100,000 load cycles (laboratory conditions). No wear that would restrict the mechanical function of the RF seals was detected in the endurance test.

General data


RF accessories Product group: Series: HF-D Soft sheild sealing Version: Spare parts Accessory type: Scope of delivery: Unassembled Material: RF felt Width: 70 mm [2.75 in] 1.5 mm [.059 in] Height: RoHS-compliant:

Compatible with

Exchangeable kits version: HF MA exchangeable kits (ATS MA): ATS MA13/HF/ESD

Technical data

Length: 325 mm [12.7 in]



Radio-frequency exchangeable kits

Part no.	Designation	Version
154013	ATS MA13/HF/AL/ESD	Radio-frequency exchangeable kit without internal interface
154113	ATS MA13/S-10/HF/AL/ESD	Radio-frequency exchangeable kit with internal interface
154014	ATS MA14/HF/AL/ESD	Radio-frequency exchangeable kit without internal interface
154114	ATS MA14/S-10/HF/AL/ESD	Radio-frequency exchangeable kit with internal interface

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162 78467, Constance, Germany Phone +49 7531 8105-0 Customer hotline +49 7531 8105-888 Fax +49 7531 8105-65 info@ingun.com







