




- Well-established test probes for contacting PCBs
- For optimal contact to the test points (e.g. pads, vias, and pins), various tip styles with various diameters and finishes are available.
- Various spring forces available as well as versions with stainless steel springs suitable for high temperatures
- Used for setting the optimum stroke conditions in the test fixture, various installation heights can be achieved by combining test probes and receptacles



1:1



### General data

|                                 |                                               |
|---------------------------------|-----------------------------------------------|
| Product group:                  | ICT / FCT (in-circuit test and function test) |
| Sub-product group:              | Standard stroke test probe                    |
| Series:                         | GKS-075                                       |
| Grid:                           | 1.91 mm [75.1 mil]                            |
| Contacting from:                |                                               |
| Magnetic:                       | Yes                                           |
| Installation type:              | Plug-in                                       |
| Quick-exchange system:          | Yes                                           |
| Adjustable installation height: | No                                            |
| Non-rotating:                   | No                                            |
| Compatible receptacle(s):       | KS-075                                        |
| Min. temperature:               | -40 °C [-40 °F]                               |
| Max. temperature:               | 80 °C [176 °F]                                |
| RoHS-compliant:                 | Yes                                           |

### Tip style data

|                     |                                                  |
|---------------------|--------------------------------------------------|
| Tip style:          | 98 90° dagger with additional cut, self-cleaning |
| Tip diameter:       | 0.64 mm [.025 in]                                |
| Tip style surface:  | A gold                                           |
| Tip style material: | 2 steel                                          |

### Electrical data

|                                        |         |
|----------------------------------------|---------|
| Current load capacity / rated current: | 3 A     |
| Typical resistance (Ri):               | 20 mOhm |

### Mechanical data

|                                 |                  |
|---------------------------------|------------------|
| Total length:                   | 33.1 mm [1.3 in] |
| Barrel diameter:                | 1.02 mm [.04 in] |
| Maximum stroke:                 | 6.35 mm [.25 in] |
| Spring pre-load:                | 0.6 N [2.15 ozf] |
| Collar height:                  | 0                |
| Spring force at working stroke: | 1.5 N [5.39 ozf] |
| Recommended working stroke:     | 4.3 mm [.169 in] |

# Test Probe

## GKS-075 298 064 A 1500

Item GKS-075-0331



**ingun**<sup>®</sup>

Partner for Future Technology



### INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162  
78467, Constance, Germany  
Phone +49 7531 8105-0  
Customer hotline +49 7531 8105-888  
Fax +49 7531 8105-65  
info@ingun.com



Prices and delivery times on request.  
Technical changes reserved. 11/25\_GB

Learn more about  
ICT/FCT Test probes



ICT/FCT TEST PROBES

ingun.com