

Receptacle

KS-075 30 M-R

Item KS-07530M-R



GO TO PRODUCT


ingun®

Partner for Future Technology

Kontaktsteckhülsen

Mit Gewinde zum Einpressen in das Trägermaterial

INGUN SELECTION



General data

Product group:
Series:
Sub-series:
Type of receptacle connection:
Press ring:
Surface area:
Collar diameter:
Collar height:
Knurl:
Vacuum-tight:
RoHS-compliant:

Receptacles (KS)
KS-075
KS-075 M screw-in version
Solder
No
Gold
1.45 mm [.057 in]
0.2 mm [.007 in]
Yes
No
Yes

Mechanical data

Total length: 32.7 mm [1.28 in]
Outer diameter: 1.32 mm [.051 in]

Mounting hole

Mounting hole in CEM1: 1.32 – 1.34 mm [.051 – .052 in]
Mounting hole in FR4: 1.32 – 1.34 mm [.051 – .052 in]

INGUN Prüfmittelbau GmbH

Max-Stromeyer-Straße 162
78467, Constance, Germany
Phone +49 7531 8105-0
Customer hotline +49 7531 8105-888
Fax +49 7531 8105-65
info@ingun.com



Prices and delivery times on request.
Technical changes reserved. 03/26_GB

Learn more about
Test probes

